

Panasonic BT-LH1710 - SPECS

Power Requirement:	AC 100 V to 240 V 50/60 Hz, 0.6 A to 0.3 A DC 12 V (11 V to 17 V) 4.0 A
Dimensions (WxHxD):	430 mm x 323.5 mm x 198mm (16-15/16" x 12-3/4" x 7-13/16") - Including stand 430 mm x 309 mm x 81.1mm (16-15/16" x 12-3/16" x 3-1/4") - Main unit only; not including stand
Weight:	7.1 kg (15.7 lbs) - Including stand 6.2 kg (13.7 lbs) - not including stand
Operating Temperature:	+5°C to +35°C (41°F to 95°F)
Operating Humidity:	20 % to 80 % (non-dew)
Storage Temperature:	—20°C to +60°C (—4°F to 140°F)
LCD Panel Size:	17.0 inch
Aspect Ratio:	15:9
Resolution:	1,280 x 768 pixels (WXGA)
Display colors:	Approx. 16,770,000 colors
Viewing Angle:	178° (both horizontal and vertical)
Video Input/Output:	Video: BNC x 2 (with through-out connector) Y/PB/PR. RGB: BNC x 6 (with through-out connector x 3) SYNC/HD: BNC x 2 (with through-out connector x 1) VD: BNC x 1 SDI: BNC x 3 (switched-out connector x 1) DVI-D (HDCP): DVI-D x 1 Vertical frequency: 50.0 Hz to 60.0 Hz Horizontal frequency: 31.5 KHz to 67.5 KHz Dot clock: 25 MHz to 165 MHz
Audio input:	Pinjack x 2 (stereo)
Headphone Output:	M3 stereo mini jack x 1
Remote:	GPI: D-SUB, 9 pin RS-232C: D-SUB, 9 pin
External DC Power Input:	XLR, 4pin
Signal Level:	Video: SYNC signal level: 0.3 Vp-p to 4.0 Vp-p HD/VD Signal level: TTL level Audio: Audio input signal level: 0.5 Vrms Speaker output: 0.5 W + 0.5 W Head phone output: 32 Ω, Variable Level SDI Embedded Audio: HD-SDI : SMPTE299M standard, 48 kHz, 8CH - synchronous/asynchronous SD-SDI : SMPTE272M standard, 48 kHz, 4CH - synchronous

Accessories:

Supplied: Power Cord Hook, Screw

Optional: Rack mount adaptor, Wall Mount Adaptor, Protective Panel